



DANGER

May be corrosive to metals. Causes serious eye irritation. May damage fertility or the unborn child.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original container. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner.

⚠️ WARNING: This product can expose you to Ethylene Oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS

Health: 2; Flammability: 1; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; Organic acid salt mixture/HMIRA Registration Number 9207;
Monocarbamide Dihydrogen Sulphate/21351-39-3; Linear Alcohol Ethoxylate/34398-01-1;
Glycerin/56-81-5

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

TOTAL SOLUTIONS®

A-R ALUMINUM & COIL CLEANER

Acid Replacement with
Acid Performance

- REPLACES HYDROFLUORIC AND SULFURIC ACIDS
- CLEANS AND BRIGHTENS CORRODED AND OXIDIZED ALUMINUM
- REMOVES DUST, GREASE, AND OXIDATION FROM COILS
- DOT NON-REGULATED

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com

DESCRIPTION: This heavy-duty acid replacement product has the performance of hydrofluoric and sulfuric acids, but is non-corrosive to skin, making it far safer to users. It is DOT non-regulated, and no EPCRA risk management plan filing is required. Contains no phosphorous.

As an aluminum cleaner and brightener, it has outstanding calcium, limescale and silicate-deposit removal properties. It quickly removes corrosion and oxidation, leaving surfaces bright and clean. It is ideal for use on aluminum trailer bodies, boats, building materials and most other exterior aluminum surfaces.

As a coil cleaner, it removes dust, dirt, grime, grease and oxidation from aluminum or copper coils as well as fins of cooling units and air conditioners. Use it regularly to clean coils for more efficient operation and lower power consumption.

DIRECTIONS: ALWAYS TEST IN AN INCONSPICUOUS AREA BEFORE USING THIS PRODUCT. Wear rubber gloves and goggles when handling. Use full strength for heavy duty cleaning. May be diluted with up to 5 parts water for maintenance or light cleaning and brightening. Brush, spray, or swab onto the surface to be cleaned, allow to penetrate soils, then rinse thoroughly with clean water. Use with care on painted surfaces.

Use plastic pails for diluting and dispose of excess solution immediately after use.

Do not use on anodized aluminum.

DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

0104.091621