



DANGER

May be corrosive to metals. Causes severe skin burns and eye damage. May cause respiratory irritation.

Keep only in original container. Do not breathe mist, spray. Avoid breathing mist, spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a doctor, a POISON CENTER if you feel unwell.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

Absorb spillage to prevent material-damage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.

⚠️ WARNING: This product can expose you to ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS

Health: 3; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER: Water/7732-18-5; Hydrogen Chloride/7647-01-0; Linear Alcohol Ethoxylate/34398-01-1; Ethoxylated Tallowamines/61791-26-2; Glycerin/56-81-5; Acid Blue 93/28983-56-4

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

RESILIENT FLOOR CARE

CONCRETE CLEANER & ETCHER

Provides Ideal Surface
Preparation Before Sealing
or Painting

· CLEANS, ETCHES AND
BLEACHES IN ONE STEP

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions[®] · 1-800-743-6417
PO Box 240014 · Milwaukee, WI 53224 · athea.com

DESCRIPTION

This concrete cleaner and etcher is specially formulated for use on concrete floors, brick, masonry block, and flagstone. It contains powerful muriatic acid to clean, etch, and whiten concrete and neutralize surface alkalinity. It should be used to prepare all concrete surfaces before painting or sealing, and to provide maximum penetration, bonding strength and durability of the coating.

DIRECTIONS

Sweep floor to remove loose soil. For heavily soiled floors, scrub with a strong detergent to remove heavy soil, grease and oil deposits and rinse. Etch the surface by using a solution of 1 gallon of this product in 5 gallons of water. Swab solution onto the surface, and scrub with a broom or brush. Allow to work for 10 minutes or until bubbling and fizzing stops. Rinse the surface thoroughly with clean water and allow to dry completely before sealing or painting.

Rinse empty containers before disposal. Use plastic containers to mix solutions. Do not store in metal pails, drums or sprayers.

DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

0140.080321