

PROFESSIONAL SECRETS TO EFFECTIVE FLOOR CARE:

- To ensure your floor finish reaches its maximum gloss potential, always apply to floors with at least two coats of a floor seal. Maximum gloss can only be achieved on smooth, level floors. Floor sealers smooth out your floors' surface imperfections to allow for maximum light reflection.
- Do not use your stripping or rinsing mop or bucket for the application of floor finishes. Always start with a clean, previously wrung-out cotton/rayon mop and bucket. Save this mop and bucket just for the application of finish.
- Always apply even, medium coats. To ensure the application of medium coats, wring out the bottom half of a fully saturated mop.
- Discard unused finish. Pouring unused finish from your bucket back into the original container can spoil the good finish.

NFPA® RATINGS

Health: 0; Flammability: 1; Reactivity: 0

CONTAINS/CAS NUMBER:

Acrylic Polymer/Proprietary; Water/7732-18-5; Diethylene Glycol Monoethyl Ether/111-90-0; Tributoxyethyl Phosphate/78-51-3; Zinc Oxide/1314-13-2

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

RESILIENT FLOOR CARE

DAZZLE

High Solids Floor Finish

· POLYMER MATRIX MAXIMIZES BURNISHING RESPONSIVENESS

· COMBINES SUPERIOR "WET LOOK" GLOSS WITH INCREDIBLE DURABILITY

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions[®] · 1-800-743-6417
PO Box 240014 · Milwaukee, WI 53224 · athea.com

DESCRIPTION

This floor finish utilizes a unique combination of synthetic polymers to produce a finish that can withstand the rigors of frequent burnishing. Designed for easy maintenance of its incredible "wet look" gloss, it displays superior scratch and scuff resistance that significantly reduces the frequency of restoration and recoating operations.

DIRECTIONS

Always apply to a floor that has previously been sealed. With a clean, rayon/cotton blend mop, apply by first "framing" the area to be finished. Use a mop to apply a line of seal around the area, then go back and fill in the "framed" area with a gentle side to side mopping motion, being certain to overlap each pass slightly. Apply seal in a thin, unbroken line. If a rectangular finish applicator is used, be certain that the applicator head has been thoroughly rinsed. Let each coat dry to the touch before recoating. Dry time is approximately 30 minutes. High humidity can prolong dry time. A fan can be used to reduce drying time. Allow the seal to set for 10 minutes before starting a fan. Do not use a fan in areas where dust could be blown onto sealer.

Apply each subsequent coat of finish using the same method outlined above. For maintenance of "wet look" gloss, burnish frequently with an UHS Electric, Battery or Propane burnisher.

MAINTENANCE OF DAZZLE: Dust mop daily using a treated dust mop. Dirt and dust can abrade and scratch your finishes destroying their natural luster. Damp mop regularly, as the highest gloss comes only from clean floors. Dirt acts as a barrier to light reflection, causing your floors to look dull and lifeless. To restore lost luster, burnish regularly.

DISPOSAL

Offer empty container for recycling. If recycling is not available, discard container in trash.



Please Recycle.

1706.033115