



DANGER

Harmful if swallowed. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection, protective clothing, protective gloves.

IF SWALLOWED: Call a doctor, a POISON CENTER if you feel unwell. Rinse mouth.

If exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell.

Store locked up.

⚠ WARNING: This product can expose you to Methyl Pyrrolidone, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS

Health: 2; Flammability: 1; Reactivity: 0

CONTAINS/CAS NUMBER: Water/7732-18-5; Acrylic Polymers/Withheld; Urethane Polymer/Withheld; Tributoxyethyl Phosphate/78-51-3; Methyl Pyrrolidone/872-50-4

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

RESILIENT FLOOR CARE

DIAMOND

Floor Sealer For Terrazzo

- WATER-BASED URETHANE-FORTIFIED FLOOR SEALER
- IDEAL FOR TERRAZZO AND POROUS STONE FLOORING
- SUPERIOR BASE COAT FOR ACRYLIC FINISHES SUBJECTED TO BURNISHING AND SPRAY BUFFING

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions% · 1-800-743-6417
PO Box 240014 · Milwaukee, WI 53224 · athea.com

FLOOR CARE TIPS:

- Do not use your stripping or rinsing mop or bucket for the application of floor sealers. Always start with a clean, previously wrung-out cotton/rayon mop and bucket. Save this mop and bucket just for the application of sealer.
- To avoid the accumulations of finish build-up in corners or on baseboards, always apply the first coat of sealer no closer than 12 inches from baseboards. Apply second and every other coat up to baseboards.
- Always apply even, medium coats. To ensure the application of medium coats, wring out the bottom half of a fully saturated mop.
Discard unused finish. Pouring unused finish from your bucket back into the original container can spoil the good finish.

This sealer has been specially formulated to solve the challenge of maintaining terrazzo and other porous stone flooring. It establishes a reversible bond with stone surfaces to ensure adhesion, and urethane modifiers give the acrylic matrix incredible strength and durability, making it an excellent base for the application of high gloss acrylic floor finishes. Two coats of this sealer levels flooring surface imperfections to maximize the gloss potential of your floor finish.

Always apply sealer to a newly stripped floor. With a clean, rayon/cotton blend mop, apply DIAMOND by first “framing” the area to be finished. Use a mop to apply a line of seal around the area to be sealed, then go back and fill in the “framed” area with a gentle side to side mopping motion, being certain to overlap each pass slightly. Apply in a thin, unbroken line. If a rectangular applicator head is used, be certain that the applicator head has been thoroughly rinsed.

Let each coat dry to the touch before recoating. Dry time is approximately 30 minutes. High humidity can prolong dry time. A fan can be used to reduce drying time. Allow the seal to set for 10 minutes before starting a fan. Do not use a fan in areas where dust could be blown onto sealer. Apply a second coat using the same method outlined above.

For floors subject to burnishing operation, apply a minimum of four coats of finish. For floors subject to spray buffing operations, apply a minimum of two coats of floor finish.

DISPOSAL: Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

1720.090321