

Diamond

Safety Data Sheet



SECTION 1: Product and company identification

Product name : Diamond
Use of the substance/mixture : Coating
Product code : 1720
Distributor's Name : CleaningChemicalSupply.com
P.O. Box 670925
Marietta, GA 30066 - USA
Phone 888-678-7489

Emergency number : Chemtrec: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification
Acute Tox. 4 (Oral) H302
Repr. 1B H360
STOT RE 2 H373

2.2. Label elements

GHS US labelling
Hazard pictograms (GHS US) :



GHS07 GHS08

Signal word (GHS US) :
Hazard statements (GHS US) :

Danger
Harmful if swallowed.
May damage fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe mist, spray.
Wash thoroughly after handling
Do not eat, drink or smoke when using this product.
Wear eye protection, protective clothing, protective gloves.
If swallowed: Call a doctor, a POISON CENTER if you feel unwell.
If exposed or concerned: Get medical advice/attention.
Get medical advice/attention if you feel unwell.
Rinse mouth.
Store locked up.
Dispose of contents/container to comply with local/regional/national/international regulations..

Precautionary statements (GHS US) :

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Urethane Polymer (Protectant)	(CAS-No.) Withheld	5.0 - 10.0	Acute Tox. 3 (Oral), H301 STOT RE 2, H373
Tributoxyethyl Phosphate (Impurity)	(CAS-No.) 78-51-3	1.0 - 5.0	Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315

Diamond

Safety Data Sheet



			Eye Irrit. 2A, H319 STOT SE 3, H335
Methyl Pyrrolidone (Impurity)	(CAS-No.) 872-50-4	1.0 - 5.0	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 1B, H360 STOT SE 3, H336 STOT SE 3, H335
Isopropanol (Impurity)	(CAS-No.) 67-63-0	1.0 - 5.0	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

All hazardous chemicals, as determined by 29 CFR 1910.1200 have been listed. A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove the victim into fresh air.
- First-aid measures after skin contact : Gently wash with plenty of soap and water.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Rinse mouth with water. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May cause damage to organs through prolonged or repeated exposure. May damage fertility. May damage the unborn child. Harmful if swallowed.
- Symptoms/effects after inhalation : None under normal use.
- Symptoms/effects after skin contact : Contact during a long period may cause light irritation.
- Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.
- Symptoms/effects after ingestion : Harmful if swallowed. Gastrointestinal complaints. Nausea. Diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Adapt extinguishing media to the environment for surrounding fires.

5.2. Special hazards arising from the substance or mixture

- Reactivity : Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

- Protective equipment : Protective goggles. Gloves. Protective clothing.
- Emergency procedures : Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers.
Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Obtain special instructions before use.
Hygiene measures : Wash thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.
Storage conditions : Keep container closed when not in use.
Incompatible products : Strong acids. Oxidizing agent.
Storage area : Meet the legal requirements. Store in a cool area. Store in a well-ventilated place. Keep locked up.
Special rules on packaging : Store in a closed container. Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tributoxyethyl Phosphate (78-51-3)

Not applicable

Methyl Pyrrolidone (872-50-4)

Not applicable

Urethane Polymer (Withheld)

Not applicable

Isopropanol (67-63-0)

ACGIH	ACGIH OEL TWA [ppm]	200 ppm
ACGIH	ACGIH OEL STEL [ppm]	400 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr; CNS impair
OSHA	OSHA PEL TWA [1]	980 mg/m ³
OSHA	OSHA PEL TWA [2]	400 ppm

8.2. Exposure controls

Personal protective equipment : Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Safety glasses. Protective clothing. Protective goggles.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Milky white liquid
Odour : Mild odor
Odour threshold : No data available
pH : 8 – 9
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : > 200 °F Closed Cup
Relative evaporation rate (butylacetate=1) : No data available

Diamond

Safety Data Sheet



Flammability (solid, gas)	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Relative vapour density at 20 °C	: No data available
Density	: 1.02 g/ml
Solubility	: Emulsifies in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: < 0.5 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO₂ are formed.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Isopropanol (67-63-0)

LD50 oral rat	5840 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	12882 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Converted value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE CLP (oral)	5840 mg/kg bodyweight
ATE CLP (dermal)	16400000 mg/kg bodyweight

Skin corrosion/irritation	: Not classified pH: 8 – 9
Serious eye damage/irritation	: Not classified pH: 8 – 9
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Isopropanol (67-63-0)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : May damage fertility or the unborn child.

Diamond

Safety Data Sheet



STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: None under normal use.
Symptoms/effects after skin contact	: Contact during a long period may cause light irritation.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: Harmful if swallowed. Gastrointestinal complaints. Nausea. Diarrhoea.
Likely routes of exposure	: Skin and eyes contact

SECTION 12: Ecological information

12.1. Toxicity

Isopropanol (67-63-0)	
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

12.2. Persistence and degradability

Isopropanol (67-63-0)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance

12.3. Bioaccumulative potential

Isopropanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
--	---

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT : Not regulated for transport

Additional information

Other information	: No supplementary information available.
-------------------	---

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Urethane Polymer	Withheld
------------------	----------

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

Methyl Pyrrolidone	872-50-4
--------------------	----------

Diamond

Safety Data Sheet



Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Methyl Pyrrolidone	872-50-4	1.0 - 5.0%
Isopropanol	67-63-0	1.0 - 5.0%

WARNING

This product can expose you to Methyl Pyrrolidone, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.