



**DESCRIPTION:** This product is an easy-to-handle liquid designed for use in fuel systems where problems exist in both the storage tank and at fireside. It reduces the viscosity of residual fuel oils and has a fluidizing effect at all temperatures, which provides more uniform and faster pumping. Sludge that typically clogs fuel strainers, nozzles, preheaters and lines is dispersed throughout the fuel. This product makes the organic/inorganic deposits in the fuel system and at the burners more friable.

This product forms a protective film on internal surfaces of storage tanks and piping to reduce corrosion and deposit build-up. It combines an effective combustion catalyst system, emulsifying agents and solvents that protect boiler tubes and refractory brickwork by deactivating the vanadium oxides and sodium salts.

Treated fuel oil burns cleaner and more completely thereby reducing emission problems associated with particulates, sulfur dioxide and sulfur trioxide. It provides superior protection against cold-end stack corrosion.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, open flames, sparks. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, spray. Take off contaminated clothing and wash it before reuse. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection, protective clothing, protective gloves.

**IF SWALLOWED:** Immediately call a doctor, a POISON CENTER. Rinse mouth. Do NOT induce vomiting. **IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **If skin irritation or rash occurs:** Get medical advice/attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **If eye irritation persists:** Get medical advice/attention. **If exposed or concerned:** Get medical advice/attention. Call a doctor, a POISON CENTER if you feel unwell.

**In case of fire:** Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Store locked up.

# TOTAL SOLUTIONS®

AUTOMOTIVE

## FUEL TREAT

Allows Fuel to Burn Clean

- EXCELLENT DISPERSING PROPERTIES

### DANGER

Flammable liquid and vapor.  
Harmful if swallowed, in contact with skin or if inhaled.

May be fatal if swallowed and enters airways.  
Causes skin irritation. May cause an allergic skin reaction.

Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause genetic defects. May cause cancer.

KEEP OUT OF REACH OF CHILDREN

**NET CONTENTS:** One Gallon (128 fl. oz.)

Manufactured By: Total Solutions®  
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

**APPLICATION:** This product is completely soluble in all fuel oils. Initial dosage is 2 gallons per 1000 gallons of fuel (1 quart per 125 gallons). Maintenance dosage is 1 quart per 1000 gallons of fuel oil (4 ounces per 125 gallons).

Add directly to the fuel oil storage tank just before the tank is refilled so that incoming oil will provide sufficient agitation and mixing.

**DISPOSAL:** Dispose of contents/container to comply with local/regional/national/international regulations.

**WARNING:** This product can expose you to benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### NEPA® RATINGS

Health: 2; Flammability: 2; Reactivity: 0

### CONTAINS/CAS NUMBER

Solvent Naphtha (Petroleum), Light Aromatic/64742-95-6; Trimethylbenzene/25551-13-7; 1,2,4-Trimethylbenzene/95-63-6; Fuel Oil Conditioner/Proprietary; Cumene/98-82-8; Corrosion Inhibitor/Proprietary; Mixed Xylenes/1330-20-7; Cymenes/25155-15-1

*For industrial and commercial use only. For additional information, see Safety Data Sheet.*



Please Recycle.

0961.031418