

Loop Treat Poly

Organic polymer-based scale & corrosion inhibitor



This liquid scale and corrosion inhibitor is designed for use in both hot or cold water closed loop recirculating systems. It features a phosphate-based formula with a polymer dispersant for anti-precipitating and sequestering harmful hard-water scale. It can be injected directly into the recirculating system through the use of a bypass feeder, or applied by use of mild steel piping and feeding equipment.

Effective Against

- Scale
- Corrosion

Features and Benefits

- Controls mineral deposits in systems using highly scaling water.
- Built-in color indicator reflects adequate pH levels.

Properties

Appearance	Red Liquid
Fragrance	Mild
Specific Gravity	1.0
pH	12.0 – 13.0
VOC Content	<0.5% by wt.

Directions

Complete directions on product label
Typical dosage is 1 gallon for every 125 gallons of capacity. Optimize the dosage by maintaining the phosphate concentration between 3.0 – 5.0 ppm.

Ingredients

Water
Potassium Hydroxide
Amino-Methylene Phosphonic Acid
Acrylamide-Acrylic Acid Copolymer
Benzotriazole

CAS Number

7732-18-5
1310-58-3
Withheld
Withheld
95-14-7


Safety

DANGER: Causes severe skin burns and eye damage. Causes serious eye damage.

DOT Shipping (Ground Transportation)

Proper Shipping Name	Corrosive liquid, basic, inorganic, n.o.s. (Potassium Hydroxide)
Class	8
ID Number	UN3266
Packing Group	II

NFPA® RATINGS



Quantities

30, 35 & 55 gallon
5 or 6 gallon
6 X 1 gallon
4 X 1 gallon



CleaningChemicalSupply.com | 1.888.678.7489 | Fax: 877.978.7489