# SAFETY DATA SHEET



CleaningChemicalSupply.com | 1.888.678.7489 | Fax: 877.978.7489

### SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

**Product ID:** 491333

Product Name: Neutrazen Fresh Linen Metered

 Revision Date:
 Jul 07, 2020
 Date Printed:
 Jul 07, 2020

 Version:
 2.0
 Supersedes Date:
 Nov 15, 2016

Manufacturer's Name: CleaningChemicalSupply.com

Address: PO Box 670925 Marietta, GA 30066

Emergency Phone: 1-800-535-5053
Information Phone Number: (888)-678-7489
Product/Recommended Uses: Air freshener

### **SECTION 2) HAZARDS IDENTIFICATION**

#### Classification

Aerosols - Category 1

Gases Under Pressure - Liquefied Gas

Eye Irritation - Category 2

Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) - Category 3

### **Pictograms**







### Signal Word

Danger

### **Hazardous Statements - Physical**

H222 - Extremely flammable aerosol

H280 - Contains gas under pressure; may explode if heated

#### **Hazardous Statements - Health**

H319 - Causes serious eye irritation H336

- May cause drowsiness or dizziness

#### **Precautionary Statements - General**

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

### **Precautionary Statements - Prevention**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

491333 Page 1 of 8

- P211 Do not spray on an open flame or other ignition source.
- P264 Wash hands thoroughly after handling.
- P280 Wear eye protection and face protection.
- P261 Avoid breathing mist, vapors or spray.
- P271 Use only outdoors or in a well-ventilated area.

# **Precautionary Statements - Response**

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER or doctor if you feel unwell.

### **Precautionary Statements - Storage**

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

P403 + P405 - Store in a well-ventilated place. Store locked up.

### **Precautionary Statements - Disposal**

P501 - Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS				
CAS	Chemical Name	% By Weight		
0000067-64-1	ACETONE	50% - 82%		
0068476-86-8	Petroleum gases, liquefied, sweetened	17% - 28%		
0000112-27-6	TRIETHYLENE GLYCOL	2% - 3%		
0000084-66-2	DIETHYL PHTHALATE	0.0% - 0.6%		
0018479-58-8	7-Octen-2-ol, 2,6-dimethyl-	0.0% - 0.5%		
0001222-05-5	Cyclopenta[g]-2-benzopyran, 1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-	0.0% - 0.4%		
0000115-95-7	hexamethyl-, 3-acetate	0.0% - 0.2%		
0000118-58-1	Benzoic acid, 2-hydroxy-, phenylmethyl ester	0.0% - 0.2%		
0026680-54-6	2,5-Furandione, dihydro-3-(octen-1-yl)-	Trace		
0000087-20-7	Benzoic acid, 2-hydroxy-, 3-methylbutyl ester	Trace		
0032388-55-9	Ethanone, 1-[(3R,3aR,7R,8aS)-2,3,4,7,8,8a-hexa-hydro-3,6,8,8-tetramethyl-1H-3a,7-methanoazulen-5-yl]-	Trace		
0000078-70-6	1,6-Octadien-3-ol, 3,7-dimethyl-	Trace		
0000093-92-5	Benzenemethanol, .alphamethyl-, 1-acetate	Trace		
0001335-46-2	lonone, methyl-	Trace		
0024851-98-7	Cyclopentaneacetic acid, 3-oxo-2-pentyl-, methyl ester	Trace		
0000151-05-3	Benzeneethanol, .alpha.,.alphadimethyl-, 1-acetate	Trace		
0068647-72-3	Terpenes and Terpenoids, sweet orange-oil	Trace		
0000106-22-9	6-Octen-1-ol, 3,7-dimethyl-	Trace		
0000080-56-8	A-PINENE	Trace		
0006683-19-8	Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)- 4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Trace		
0008000-48-4	Oils, eucalyptus	Trace		
0000470-82-6	2-Oxabicyclo[2.2.2]octane, 1,3,3-trimethyl-	Trace		

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

### **SECTION 4) FIRST-AID MEASURES**

491333 Page 2 of 8

#### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

If exposed/feel unwell/concerned: Call a POISON CENTER or doctor.

Eliminate all ignition sources if safe to do so.

#### **Eye Contact**

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

#### Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

#### Ingestion

Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

#### Most Important Symptoms/Effects, Acute and Delayed

No data available.

#### Indication of Immediate Medical Attention and Special Treatment Needed

No data available.

### **SECTION 5) FIRE-FIGHTING MEASURES**

### Suitable Extinguishing Media

Dry chemical, foam, carbon dioxide. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

Do not direct a solid stream of water or foam into hot, burning pools. This may result in frothing and increased fire intensity.

### **Unsuitable Extinguishing Media**

No data available.

### Specific Hazards in Case of Fire

Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Product is highly flammable and forms explosive mixtures with air, oxygen, and all oxidizing agents. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back.

During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a build up of internal pressures. Cool with water.

Empty Containers retain product residue which may exhibit hazards of material; therefore do not pressurize, cut, glaze, weld or use for any other purposes.

Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors.

### **Fire-Fighting Procedures**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

#### **Special Protective Actions**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

### **SECTION 6) ACCIDENTAL RELEASE MEASURES**

### **Emergency Procedure**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

491333 Page 3 of 8

### **Recommended Equipment**

Wear liquid tight chemical protective clothing in combination with positive pressure self-contained breathing apparatus (SCBA).

#### **Personal Precautions**

Avoid breathing vapor. Avoid contact with skin, eye or clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

#### **Environmental Precautions**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

### Methods and Materials for Containment and Cleaning up

Absorb liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

### **SECTION 7) HANDLING AND STORAGE**

#### General

Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally.

#### **Ventilation Requirements**

Use in a well-ventilated place.

### **Storage Room Requirements**

Store and use in a cool, dry, well-ventilated area. Do not store above 120°F. See product label for additional information.

### **SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Eye Protection**

Wear safety glasses with side shields. Eyewash stations and showers should be available in areas where this material is used and stored.

#### Skin Protection

Use solvent-resistant protective gloves for prolonged or repeated contact.

### **Respiratory Protection**

Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

#### **Appropriate Engineering Controls**

Ventilation should be sufficient to prevent inhalation of any vapors.

Chemical Name	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)
ACETONE	2400	1000				1		250
A-PINENE								20
DIETHYL PHTHALATE							5	
Petroleum gases, liquefied, sweetened	2000	500				1		

Chemical Name	NIOSH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)
ACETONE			500	A4	URT & eye irr; CNS impair	A4; BEI	590	250
A-PINENE				A4	Lung irr	DSEN; A4		
DIETHYL PHTHALATE				A4	URT irr	A4	5	
Petroleum gases, liquefied, sweetened								

491333 Page 4 of 8

Chemical Name	NIOSH STEL (mg/m3)	OSHA STEL (ppm)	NIOSH Carcinogen
ACETONE			
A-PINENE			
DIETHYL PHTHALATE			
Petroleum gases, liquefied, sweetened			

<sup>(</sup>C) - Ceiling limit, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS -Central nervous system, DSEN - Dermal sensitization, impair - Impairment, irr - Irritation, URT - Upper respiratory tract

### **SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES**

### **Physical and Chemical Properties**

Density	5.98 lb/gal
Density VOC	1.64 lb/gal
% VOC	27.41%

Appearance N.A
Odor Description Fresh

### **SECTION 10) STABILITY AND REACTIVITY**

#### Stability

Stable under normal storage and handling conditions.

#### **Conditions to Avoid**

Avoid heat, sparks, flame, high temperature and contact with incompatible materials.

Dropping containers may cause bursting.

### **Incompatible Materials**

Avoid strong oxidizers, reducers, acids, and alkalis.

### **Hazardous Reactions/Polymerization**

Will not occur.

### **Hazardous Decomposition Products**

No data available.

### **SECTION 11) TOXICOLOGICAL INFORMATION**

#### Skin Corrosion/Irritation

No data available.

## Likely Route of Exposure

Inhalation, ingestion, skin absorption.

### Serious Eye Damage/Irritation

Causes serious eye irritation.

### Carcinogenicity

No data available.

### **Germ Cell Mutagenicity**

No data available.

### **Reproductive Toxicity**

No data available.

491333 Page 5 of 8

### Respiratory/Skin Sensitization

No data available.

### **Specific Target Organ Toxicity - Single Exposure**

May cause drowsiness or dizziness

### **Specific Target Organ Toxicity - Repeated Exposure**

No data available.

### **Aspiration Hazard**

No data available.

#### **Acute Toxicity**

No data available.

### **Potential Health Effects - Miscellaneous**

0000067-64-1 ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

### **SECTION 12) ECOLOGICAL INFORMATION**

### **Toxicity**

No data available.

#### Persistence and Degradability

No data available.

#### **Bio-Accumulative Potential**

No data available.

#### **Mobility in Soil**

No data available.

### **Other Adverse Effects**

No data available.

### **SECTION 13) DISPOSAL CONSIDERATIONS**

### **Waste Disposal**

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

### **SECTION 14) Transport Information**

Display Order	IATA Information	IMDG Information	U.S. DOT Information
UN number:	UN1950	UN1950	UN1950
Proper shipping name:	Aerosols, flammable	Aerosols	Aerosols
Hazard class:	2.1	2.1	2.1
Packaging group:	N.A.	N.A.	N.A.
Note / Special Provision:	(LTD QTY)	(LTD QTY)	(LTD QTY)

491333 Page 6 of 8

# **SECTION 15) REGULATORY INFORMATION**


CAS	Chemical Name	% By Weight	Regulation List
0000067-64-1	ACETONE	50% - 82%	CERCLA, SARA312, VOC exempt, TSCA, RCRA
0068476-86-8	Petroleum gases, liquefied, sweetened	17% - 28%	SARA312, VOC, TSCA
0000112-27-6	TRIETHYLENE GLYCOL	2% - 3%	SARA312, VOC, TSCA
0000084-66-2	DIETHYL PHTHALATE	0.0% - 0.6%	CERCLA, SARA312, TSCA, RCRA
0018479-58-8	7-Octen-2-ol, 2,6-dimethyl-	0.0% - 0.5%	SARA312, TSCA
0001222-05-5	Cyclopenta[g]-2-benzopyran, 1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-	0.0% - 0.4%	SARA312, TSCA
0000115-95-7	hexamethyl-, 3-acetate	0.0% - 0.2%	SARA312, TSCA
0000118-58-1	Benzoic acid, 2- hydroxy-, phenylmethyl	0.0% - 0.2%	SARA312, TSCA
0026680-54-6	2,5-Furandione, dihydro-3- (octen-1-yl)-	Trace	SARA312, TSCA
0000087-20-7	Benzoic acid, 2-hydroxy-, 3- methyl-butyl ester	Trace	SARA312, TSCA
0052474-60-9	3-Cyclohexene-1-carboxaldehyde, 1-methyl-3-(4-methyl-3-penten-1-yl)-	Trace	SARA312, TSCA
0032388-55-9	Ethanone[(3R,3aR,7R,8aS)-2,3,4,7, 8,8a-hexahydro-3,6,8,8- tetramethyl- 1H-3a,7-	Trace	SARA312, TSCA
0000078-70-6	nethanoazulen-5-yij- 1,6-Octadien-3-ol, 3,7-dimethyl-	Trace	SARA312, TSCA
0001365-19-1	Linalool oxide	Trace	SARA312, TSCA
0010339-55-6	1,6-Nonadien-3-ol, 3,7-dimethyl-	Trace	SARA312, TSCA
0000093-92-5	Benzenemethanol, .alphamethyl-, 1-acetate	Trace	SARA312, TSCA
0001335-46-2	lonone, methyl-	Trace	SARA312, TSCA
0024851-98-7	Cyclopentaneacetic acid, 3- oxo-2-pentyl-, methyl ester	Trace	SARA312, TSCA
0000151-05-3	Benzeneethanol, .alpha.,.alpha. -dimethyl-, 1-acetate	Trace	SARA312, TSCA
0068647-72-3	Terpenes and Terpenoids, sweet orange-oil	Trace	SARA312, TSCA
0000106-22-9	6-Octen-1-ol, 3,7-dimethyl-	Trace	SARA312, TSCA
0000080-56-8	A-PINENE	Trace	SARA312, VOC, TSCA
0008022-15-9	Oils, lavandin	Trace	SARA312, TSCA
0006683-19-8	Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxy-phenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Trace	SARA312, TSCA
0008000-48-4	Oils, eucalyptus	Trace	SARA312, TSCA
0000470-82-6	2-Oxabicyclo[2.2.2]octane, 1,3,3-trimethyl-	Trace	SARA312, TSCA

491333 Page 7 of 8

### **SECTION 16) OTHER INFORMATION**

#### Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.



(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

### **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

491333 Page 8 of 8