

SPECCRETE® SPECCOPATCH RS

ALL PURPOSE CONCRETE PATCHING MORTAR



FAST SETTING • SHAPEABLE & SHAVEABLE • TENACIOUS BOND
VERSATILE USES FOR HORIZONTAL, VERTICAL OR OVERHEAD REPAIRS

DIRECTIONS: SURFACE PREPARATION: All areas to be patched shall be clean and free of oil, grease, dirt, deteriorated concrete and any additional contaminants. Abrade or acid etch slick surfaces to ensure proper bond. Clean, prepare and prime any exposed steel per I.C.R.I. guidelines. Always pre-wet the substrate to a S.S.D. (saturated surface dry) condition with no standing water on the surface.

MIXING: Mix only as much material as can be placed in 10 minutes. Place approx. **3.25 quarts (0.81 gal.)** of water in a mixing pail and slowly add the 45 lb. of Speccrete® Speccopatch RS while continuously mixing with a mechanical low speed drill and paddle mixer. Higher quantities of bags may be mixed in a mortar mixer to speed the mixing process for larger jobs. Mix Speccrete® Speccopatch RS to a uniform, lump free consistency for a minimum of 60 seconds. A thick, creamy putty-like texture (zero slump) is considered ideal working consistency.

APPLICATION: Apply Speccrete® Speccopatch RS at a 1/4 inch minimum up to 0.75 inch (overhead) and 2.0 inch (vertical) maximum thickness per lift. If applying in successive lifts, allow preceding lift to stiffen to harden before applying fresh material. Refer to technical data sheet for applications over 2.0 inches requiring possible aggregate addition. Always overfill the area to be patched. Force Speccrete® Speccopatch RS into the area to be patched by trowel and form to the intended shape. Once initial set has occurred, shave the patch to the desired finish. Always shave towards the bond lines. Finish with a steel trowel. Clean tools with water immediately after use.

CAUTIONS: Do not feather edge. Do not add previously mixed material to new batches. Do not re-temper or overwork the mix. Do not add excessive water. Do not apply to frozen or frost filled surfaces. Refer to technical data sheet for additional cautions.

NET WEIGHT: 45 lb (20.45 kg)

COVERAGE: 22 sq. ft @ 1/4 inch thick

YIELD: 0.40 cu.ft



CleaningChemicalSupply.com

[888-678-7489](tel:888-678-7489)

