



DANGER

Flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer.

DESCRIPTION: Concentrated anti-gel additive keeps all types of fuel and diesel oils flowing in cold weather. By interfering with the formation of wax crystals in the fuel, the pour point of the fuel can be reduced by as much as 25°F. Fuel flows easily through lines and filters – without the need for tank heaters.

Eliminates dangerous failures of oil fired boilers, furnaces and diesel truck and generator engines in cold weather.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, open flames, sparks. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves.

IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Rinse mouth. Do NOT induce vomiting. **IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **If skin irritation occurs:** Get medical advice/attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **If eye irritation persists:** Get medical advice/attention. **If exposed or concerned:** Get medical advice/attention. Call a doctor, a POISON CENTER if you feel unwell.

In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

AUTOMOTIVE

DIESEL FUEL ANTI-GEL

For Use in Diesel Fuels and
All Grades of Fuel Oil

- REDUCES POUR POINT AND INHIBITS GELLING
- STABILIZES FUEL

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

DIRECTIONS: Add to all grades of fuel at the rate of 12 ounces per 150 gallons. This dosage will lower the pour point of most residual fuels by approximately 20°F. In some cases, additional treatment will lower the pour point by several more degrees.

For best results, the fuel should be at least 10°F above normal pour point when anti-gel additive is blended in.

This diesel fuel additive complies with the Federal low sulfur content requirements for use in diesel motor vehicles and non-road engines.

⚠ WARNING: This product can expose you to benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

DISPOSAL: Dispose of contents/container to comply with local/regional/national/international regulations.

NFPA® RATINGS

Health: 2; Flammability: 2; Reactivity: 0

CONTAINS/CAS NUMBER:

Solvent Naphtha (Petroleum), Light Aromatic/64742-95-6; Benzene, Trimethyl- 25551-13-7; 1,2,4-trimethylbenzene/95-63-6; Heavy Aromatic Solvent/64742-94-5; Cumene/98-82-8; Mixed Xylenes/1330-20-7; Naphthalene/91-20-9; Kerosene (petroleum) hydrodesulphurised/64742-81-0; Cymenes/25155-15-1



Please Recycle.

0654.010721