Convert

Sprayable Rust Converter



If it's worth protecting, it deserves Convert. Convert sprayable rust converter instantly converts rust to a non-rusting surface. Convert sprayable rust converts instantly bonds with rust and transforms it to a non-rusting, paintable surface as well as preventing future rust. It saves you the effort of sanding rust all the way down to bare metal. Convert is completely safe and easy to apply.

llse on:

Structures Note: Do not use wi	Machinery Equipment water-based paints	t ● Vehicles ● F	Pailings • Marine Applications	And More	
Protects agaEffects of weat		• Sun	Salt spray		
Features and Benefits • Easy to use, non-flammable, low VOC • Water based treatment • Approved for use on all non-food contact surfaces • Protects against future corrosion • Non-toxic and emits no harmful fumes					
PropertiesAppearanceBeige LiquidFragranceBlandReady to useYespH1.5-3.0Shelf Life9 months for unopened propertiesProtect fromFreezing temperatures or temperature above 100 °F	Directions Complete directions on product label Apply two coats allowing at least 20 minutes drying time between coats. Allow 48 hours of cure time before applying an oil-based paint.				
	9 months for unopened product Freezing temperatures or	uct porous surfac	One gallon will cover 200 - 300 square feet of a smooth non- porous surface. Irregular, porous surfaces will require a heavier application rate.		

Ingredients

Water	7732-18-5
Acrylic copolymer latex	Proprietary
2-butoxyethanol	111-76-2
Tannic acid	1401-55-4
Propylene glycol	57-55-6

Safety

Keep out of the reach of children

DOT Shipping (ground transportation)


Proper Shipping Name: Class: None ID Number: None Package Group: None

None

Quantities 5 or 6 gallon

6x1 gallon 4x1 gallon





CAS Number